


- Swinghandle in accordance with **RC2 ENV 1630 standard**
- The lock has the **security level** in accordance with **DIN EN 50102**
- The handle and housing **resistant to strain**.

- Lock has a protection class **IP 66**
- Lock from material **ZAMAK 5**
- Patented insert to order separately, check pg. 1C-1, 1C-2

All components to order separately for version under a cap and a cogwheel mechanism are shown check pg. 1B-25.

TYPE OF LOCK	VERSION	COMPONENTS	MATERIAL	FINISH [C]
				RAL 9005
RS980.N	For a cap	Housing, Handle, Sliding dust cover	ZAMAK 5	04
RS980/U.N		Housing, Handle, Sliding dust cover, Padlock device		
RS980.M	For a cogwheel mechanism	Housing, Handle, Sliding dust cover	ZAMAK 5	04
RS980/U.M		Housing, Handle, Sliding dust cover, Padlock device		



Swinghandle cooperates with PANIK / ZWP.001, ZWP.002 and ZW locks

TYPE OF LOCK	COMPONENTS	MATERIAL	FINISH [C]	
			RAL 9005	RAL 7035
RS983	Housing, Handle	ZAMAK 5	04	05

How to order:

Type of lock

Finish

where:

Ts - door thickness

Lock compatible with tongues of group: 15, 16, 19, 21, 35, 36, JK1-10018-G-M, JK2-10018-G-M (pg. 1C-12 to 1C-21)

The lock works with the cylinders: WRS-B.001 (pg. 1C-1)