



### Specification

**TYPE A** - 4 holes for countersunk screws

**TYPE B** - version with 4 threaded pins

**TYPE C** - version with 2 threaded pins and 2 holes

### INFORMATION

Type A and C: use DIN 965 screws

Pin made of AISI 304 stainless steel

M6 screws made of AISI 304 stainless steel

M8 screws made of galvanized steel

\* possibility to order with M5x8 pins

### Material: ZAMAK 5

CATALOG NO.	TYPE	L1	L2	c	h1	b1	b2	b3	t1	t2	d1	d2	d3	FINISH
3.ZN60.001-01	A	40	40	-	-	12,5	12,5	25	9	5	4	5,4	10	Chrome
3.ZN60.001-04	A	40	40	-	-	12,5	12,5	25	9	5	4	5,4	10	RAL9005
3.ZN60.001-05	A	40	40	-	-	12,5	12,5	25	9	5	4	5,4	10	RAL7035
3.ZN60.002-01*	B	40	40	M5	12,5	12,5	12,5	25	9	5	4	-	-	Chrome
3.ZN60.002-04*	B	40	40	M5	12,5	12,5	12,5	25	9	5	4	-	-	RAL9005
3.ZN60.002-05*	B	40	40	M5	12,5	12,5	12,5	25	9	5	4	-	-	RAL7035
3.ZN60.004-01*	C	40	40	M5	12,5	12,5	12,5	25	9	5	4	5,4	10	Chrome
3.ZN60.004-04*	C	40	40	M5	12,5	12,5	12,5	25	9	5	4	5,4	10	RAL9005
3.ZN60.004-05*	C	40	40	M5	12,5	12,5	12,5	25	9	5	4	5,4	10	RAL7035
3.ZN65.001-01	A	50	50	-	-	15	15	30	11	6	6	6,3	11,5	Chrome
3.ZN65.001-04	A	50	50	-	-	15	15	30	11	6	6	6,3	11,5	RAL9005
3.ZN65.001-05	A	50	50	-	-	15	15	30	11	6	6	6,3	11,5	RAL7035
3.ZN65.002-01	B	50	50	M6	12,5	15	15	30	11	6	6	-	-	Chrome
3.ZN65.002-04	B	50	50	M6	12,5	15	15	30	11	6	6	-	-	RAL9005
3.ZN65.002-05	B	50	50	M6	12,5	15	15	30	11	6	6	-	-	RAL7035
3.ZN65.003-01	C	50	50	M6	12,5	15	15	30	11	6	6	6,3	11,5	Chrome
3.ZN65.003-04	C	50	50	M6	12,5	15	15	30	11	6	6	6,3	11,5	RAL9005
3.ZN65.003-05	C	50	50	M6	12,5	15	15	30	11	6	6	6,3	11,5	RAL7035
3.511.11	A	60	60	-	-	18	18	36	15	8	8	8,4	14,5	Chrome
3.511.12	A	60	60	-	-	18	18	36	15	8	8	8,4	14,5	RAL9005
3.511.21	B	60	60	M8	14,8	18	18	36	15	8	8	-	-	Chrome
3.511.22	B	60	60	M8	14,8	18	18	36	15	8	8	-	-	RAL9005
3.511.31	C	60	60	M8	14,8	18	18	36	15	8	8	8,4	14,5	Chrome
3.511.32	C	60	60	M8	14,8	18	18	36	15	8	8	8,4	14,5	RAL9005

### Material: STAINLESS STEEL AISI 316

CATALOG NO.	TYPE	L1	L2	c	h1	b1	b2	b3	t1	t2	d1	d2	d3	FINISH
3.ZN60.001SN	A	40	40	-	-	12,5	12,5	25	9	5	4	5,2	11,5	-
3.ZN60.002SN	B	40	40	M5	12	12,5	12,5	25	9	5	4	-	-	-
3.ZN65.001SN	A	50	50	-	-	15	15	30	11,5	6	6	6,3	13,5	-
3.ZN65.002SN	B	50	50	M6	12	15	15	30	11,5	6	6	-	-	-
3.511.001SN	A	60	60	-	-	18	18	36	15	8	8	8,2	18	-
3.511.002SN	B	60	60	M8	14	18	18	36	15	8	8	-	-	-

### Material: POLYAMIDE

CATALOG NO.	TYPE	L1	L2	c	h1	b1	b2	b3	t1	t2	d1	d2	d3	FINISH
3.511.13	A	60	60	-	-	18	18	36	15	8	8	8,4	16,8	RAL 9005