









	Design (section of gasket)	Code	Clamping range [mm]	Colour	Material	Sales unit
		UT-4	1,0-4,0	C	PVC	100 m
		UT-4.2	1,0-1,5	C	PVC	100 m
		UT-4.3.01	1,0-2,0	C	PVC	100 m
		UT-4.3.02	1,0-2,0	B	PVC	100 m
		UT-4.3.06	1,0-2,0	S	PVC	100 m
 		UT-4.4.01	1,0-4,0	C	PVC	100 m
		UR-4.4.01 *	1,0-4,0	C	EPDM	100 m
		UT-4.4.02	1,0-4,0	B	PVC	100 m
		UT-4.4.04	1,0-4,0	SC	PVC	100 m
		UT-4.4.05	1,0-4,0	SJ	PVC	100 m
		UT-4.5.2	1,0-2,5	C	PVC	100 m
		UT-4.5.4	2,0-4,0	C	PVC	100 m
		UT-4.5.6	4,0-6,0	C	PVC	100 m
		UT-4.6	1,0-4,0	C	PVC	100 m

C - black, B - white, S - grey, SJ - bright grey, SC - dark gray

* Time of delivery 5-6 weeks



.NBR - nitrile rubber, compliant with oil-resistance standard



.EMV - compliant with electromagnetic shielding standard



.VDI - compliant with hygienic standard VDI 6022 (HVAC)



.UR - compliant with railway standard EN 45545-2 (fire, smoke, toxicity)



.UL - compliant with US standard UL 50



- EPDM



- PVC