









Profile uszczelniające

	Przekrój uszczelki	Nr uszczelki	Szerokość rantu	Kolor	Materiał	Minimalne zamówienie
		UT-4	1,0-4,0	C	PVC	100 m
		UT-4.2	1,0-1,5	C	PVC	100 m
		UT-4.3.01	1,0-2,0	C	PVC	100 m
		UT-4.3.02	1,0-2,0	B	PVC	100 m
		UT-4.3.06	1,0-2,0	S	PVC	100 m
 		UT-4.4.01	1,0-4,0	C	PVC	100 m
		UR-4.4.01 *	1,0-4,0	C	EPDM	100 m
		UT-4.4.02	1,0-4,0	B	PVC	100 m
		UT-4.4.04	1,0-4,0	SC	PVC	100 m
		UT-4.4.05	1,0-4,0	SJ	PVC	100 m
		UT-4.5.2	1,0-2,5	C	PVC	100 m
		UT-4.5.4	2,0-4,0	C	PVC	100 m
		UT-4.5.6	4,0-6,0	C	PVC	100 m
		UT-4.6	1,0-4,0	C	PVC	100 m

C - czarny, B - biały, S - szary, SJ - szary jasny SC - szary ciemny

* Czas dostawy 5-6 tygodni, profile na zamówienie

 .NBR - kauczuk nitrilowy, spełniające normę odporności na oleje

 .EMV - spełniające normę ekranowania elektromagnetycznego

 .VDI - spełniające normę higieniczną VDI 6022 (HVAC)

 .UR - spełniające normę kolejową EN 45545-2 (ogień, dym, toksyczność)

 .UL - spełniające normę amerykańską UL 50

 - EPDM

 - PVC